

AMENDMENTS TO THE SPECIFICATION

Page 16, second full paragraph:

The image quality control area 41 displays control buttons or sliders for manual image quality control, including a print finish designation button 59, a density control slider 60, a color control slider 61, a contrast control slider 62, a sharpness control slider 63, a soft focus effect control slider 64, and a saturation control slider 65. The control buttons are operated by clicking the pointer 44 thereon, whereas the sliders are operated by dragging their knobs to an appropriate position through the mouse 27.

Page 22, first full paragraph:

When the recording sheet size and the template are selected on the print size button 80, a crop boundary 84 specific to the selected paper size or the template is displayed on the image 46 to synthesize that has been selected and displayed on the main display area 37, as shown in Fig.

3. The crop boundary 84 is provided with a triangular mark ~~84~~ 86 that indicates an upper side of the crop boundary 84. By gripping this mark 84 through the mouse 27, the crop boundary 84 may be moved on the image 46 to synthesize.

Page 29, first full paragraph:

The operator clicks on the thumbnail of the image to select for pasting, e.g. on the thumbnail ~~47b~~ 48b in this instance. Then, the selected image is displayed as a second image 88 in a large size on the main display area 37, and the crop boundary 84 corresponding to the inner frame 47b is displayed on the second image 88. It is possible to control the image quality of the second image 88 by use of the control buttons and sliders of the image control area 41, while the second image 88 is displayed on the main display area 37. If the operator already decides the

Amendment under 37 C.F.R. § 1.111
U.S. Application No. 09/883,225

image to select before reading out all the stored images from the storage card, it is possible to

*B3
cond.* designate that image and read out merely image data of that image.
